

# 19-70017 : MANUAL, INSTALLATION NOTES FOR 2-US MTS-DL 40/60 HYDRAULIC KITS

## INSTALLATION SCHEMATIC W/PART IDENTIFICATION

**CAUTION:** DAMAGE TO BYPASS FILTER KIT, EQUIPMENT OR BODILY INJURY MAY OCCUR IF INSTRUCTIONS IN INSTALLATION NOTES NOT FOLLOWED; OR IF BYPASS FILTER KIT MATERIALS ARE MODIFIED IN ANY FASHION; OR INSTALLED ON EQUIPMENT NOT INTENDED FOR PRODUCT USAGE; OR IF BYPASS FILTER KIT IS INSTALLED IN AN OTHERWISE UNINTENDED MANNER. TAKE CARE TO ENSURE PRESSURIZED OIL SUPPLY TO BYPASS FILTER SYSTEM DOES NOT EXCEED PRESSURE LIMITATIONS OF BYPASS FILTER SYSTEM'S MAXIMUM INPUT PRESSURE (5,000 PSI W/PRESSURE REDUCING VALVE KIT INSTALLED). VERIFY DESIGNATED PRESSURIZED OIL SUPPLY PORT PRESSURE LEVEL WITH SUITABLE GAGE, AS RECOMMENDED OR FURNISHED BY THE EQUIPMENT OEM. ENSURE EQUIPMENT RETURN LOCATION FOR RETURN OIL FLOW OUT OF INSTALLED BYPASS FILTER UNIT(S) & OIL FLOW FROM RELIEF PRESSURE OVER-FLOW LINE (PLUMBED OUT OF PRESSURE REDUCING VALVE KIT) IS CONNECTED TO A NON-PRESSURIZED LOCATION (I.E. HYDRAULIC OIL RESERVOIR)- WITH PRESSURE READINGS AT OR NEAR 0 PSI TO AVOID PRESSURE BUILD-UP IN BYPASS FILTER SYSTEM- VERIFY PRESSURE LEVEL AT DESIGNATED OIL RETURN PORT WITH SUITABLE GAGE, AS RECOMMENDED OR FURNISHED BY THE EQUIPMENT OEM

